



# Bata Industrials®

## IMPROVING WORKING LIVES

- Nubuck leather/abrasion resistant TPU toecap
- Boa® closure system
- Steel midsole + Steel toecap, XW fitting
- PU cushioning footbed
- Bata Cool Comfort®-lining + 200 gr Thinsulate
- PU cushioning midsole with rubber outsole
- US size range 7,8-11,12,13,14&15
- CSA standard: Z.195-09 ESR / ASTM F 2413-11

- Cuir nubuck/bout recouvert en TPU
- Système de fermeture Boa®
- Semelle anti-perforation métallique
- Embout métallique, chaussant XW
- Semelle PU amortisseur
- Doublure Bata Cool Comfort® + 200 g Thinsulate
- Semelle intermédiaire en PU/semelle d'usure en caoutchouc
- Pointures américaines 7,8-11,12,13,14&15
- CSA standard: Z.195-09 ESR / ASTM F 2413-11

## STYLE 561



### Sole Functional design

1. Larger profile blocks
2. Flex grooves in forefoot increase flexibility and minimize fatigue
3. External torsion tech for stability
4. Flex grooves / tunnel in heel design to absorb shock
5. Grip at the heel on
6. Grip at the toe off
7. Durable rubber outsole - oil, acid and heat resistance 300c.
8. Multi directional slip resistant sole

### Semelle au design fonctionnel

1. Blocs du profil de la semelle plus larges
2. Rainures flexibles dans l'avant-pied augmentent la flexibilité et réduisent au minimum la fatigue
3. Tech de torsion externe pour plus de stabilité
4. Rainures flexibles / échancrure dans le talon pour l'amortissement du choc
5. Antidérapant au niveau du talon
6. Antidérapant sur la pointe
7. Semelle de marche en caoutchouc résistante aux hydrocarbures, aux acides et isolante jusqu'à 300°C
8. Propriétés antidérapantes multidirectionnelles



BATA shoe agent - Hugh Fox & Sons Inc.

44 Blenheim Road, Cambridge, Ontario Canada, N1S 1E8

Ph: 226-220-4363 Fax: 519-620-0932

Email: [hugh.fox@bata.com](mailto:hugh.fox@bata.com) / [www.bataindustrials.com](http://www.bataindustrials.com) / [www.bataindustrials.ca](http://www.bataindustrials.ca)

